



Corrigendum

Corrigendum to “A High-Efficiency Two-Stroke Engine Concept: The Boosted Uniflow Scavenged Direct-Injection Gasoline (BUSDIG) Engine with Air Hybrid Operation” [Engineering 5 (2019) 535–547]



Xinyan Wang\*, Hua Zhao

*Centre for Advanced Powertrain and Fuels, Brunel University London, Uxbridge UB8 3PH, UK*

The authors regret to inform that several numbers/variables are mistaken due to clerical errors.

1. In the first paragraph of Section 4.4, “For the short duration design with an ED of 98 °CA, the EVO was gradually delayed from 101 to 141 °CA”, where “101” should be “107.”

2. In the figure caption of Fig. 15, where “ $r_{1/E}$ ” should be “ $\alpha_{1/E}$ .”

The authors would like to apologize for any inconvenience caused.

DOI of original article: <https://doi.org/10.1016/j.eng.2019.03.008>

\* Corresponding author.

E-mail address: [xinyan.wang@brunel.ac.uk](mailto:xinyan.wang@brunel.ac.uk) (X. Wang).

<https://doi.org/10.1016/j.eng.2019.08.004>

2095-8099/© 2019 THE AUTHORS. Published by Elsevier LTD on behalf of Chinese Academy of Engineering and Higher Education Press Limited Company. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).