

An Intelligent System for Risk Classification of Stock Investment Projects

Antoaneta Serguieva^a, Tatiana Kalganova^b, Tariq Khan^a

^aDepartment of Business and Management

^bDepartment of Electronic and Computer Engineering

Brunel University, Uxbridge UB8 3PH, UK

Email: Antoaneta.Serguieva@brunel.ac.uk

The proposed paper demonstrates that a hybrid fuzzy neural network can serve as a risk classifier of stock investment projects. The training algorithm for the regular part of the network is based on bidirectional incremental evolution proving more efficient than direct evolution. The approach is compared with other crisp and soft investment appraisal and trading techniques, while building a multimodel domain representation for an intelligent decision support system. Thus the advantages of each model are utilised while looking at the investment problem from different perspectives. The empirical results are based on UK companies traded on the London Stock Exchange.

Keywords: finance, bidirectional incremental evolution, multimodel knowledge representation.

1 Introduction

Standard investment appraisal techniques have been continuously revised. The criteria have been reoptimised due to investment irreversibility [14] and the impact of a project on the investor's total risk [45]. It has been realised that the removal of any of the perfect market assumptions destroys the foundation and reduces the effectiveness of the methods. Alternatively, a fuzzy criterion does not attempt to cope with a specific drawback of standard techniques but permits into the calculations as much uncertainty as the market could possibly suffer. The outcome is an effective method under restricted information, uncertain data and market imperfections. A fuzzy criterion and investment rating technique are first introduced in [5], then considered in a broader framework of accumulation and discount models in [10], and recently modified with an alternative fuzzification of the project duration in [30]. While those studies are theoretical in nature, the empirical results are a major emphasis in [23,40,42,43], where stock projects are evaluated and UK companies traded on the London Stock Exchange are considered. Simultaneously, the analysis of the empirical solutions to the fuzzy criterion facilitates there the induction of three general conclusions. An investment risk measure, an estimate of the project robustness towards market uncertainty modelled with the fuzzified data, and an alternative ranking technique based on the two measures.

When compared with previous studies, the proposed paper demonstrates the following advantages. First, nine representative projects are chosen from the database employed in [40], thus consistently emphasising the empirical results. Second, the projects are rated according to a modification of the risk measure suggested there, extending further the developed method. Third, a fuzzy-valued criterion is formulated and a regular fuzzy neural network, trained with a genetic algorithm, approximates its solution. Hence, the benefits of various soft techniques are blended to achieve a synergy in handling the investment appraisal problem. In comparison, [5,6,10,23,30] only study fuzzy criteria. Forth, the network is hybridised to discriminate between low-risk and high-risk projects. The threshold is agent-dependent, communicating the acceptable levels of risk. The variety of market agents work within diverse risk ranges. In the extreme, the behaviour of an investment fund differs from the behaviour of an individual investor. Consequently, an agent-dependent threshold will benefit the decision-maker. Fifth, an efficient training algorithm is suggested for the regular part of the fuzzy

network. Genetic algorithms are a promising tool in training fuzzy networks and recent studies successfully apply direct evolution to optimise the fuzzy weights in small regular networks resembling particular types of univariable fuzzy functions [8]. In comparison, here the network approximates a multivariable criterion and the number of nodes depends on the investment horizon. The complexity of the problem requires a corresponding evolutionary strategy and the implementation of bidirectional incremental evolution is suggested. Incremental strategy has been already applied to evolve neural networks controlling a robot's motion [18]. In addition to incremental evolution, the bidirectional strategy further incorporates divide-and-conquer evolution. Thus the complex task is first gradually divided into simpler subtasks, then each subtask is evolved separately, and lastly the evolved subsolutions are merged incrementally to optimise the overall solution. The technique allows overcoming the stalling effect in direct evolution and has already proved more efficient in evolving logic functions [24].

Finally, the developed classifier is compared with other classical and soft investment appraisal and trading methods, and the advantages of each approach are utilised while building a multimodel knowledge domain for an intelligent decision support system. This will allow looking at the investment problem from various conceptual or purpose angles and choosing an adequate technique for each situation. A beneficial feature of such knowledge organisation, in comparison with single-model representations, is the flexibility it offers in overcoming specific model drawbacks. Navigating within a space of multiple models has been already applied to technical and medical domains [4,26,27,29]. There, the increased capability of the related intelligent systems in supporting users through various tasks is examined, and particularly in overcoming limitations inherent in mono-model approaches. In the investment domain, such system will enhance the ability of the decision-maker to analyse projects from multiple perspectives, and will support him in solving problems with varying objectives and complexity.

The proposed approach is developed for the following reasons. First, there have been suggested fuzzy techniques for investment appraisal and based on them ranking procedures [5,40], but no investment classifier is yet considered. Therefore, a decision would only be taken after applying the fuzzy criterion to all available projects, then rating them accordingly, and finally choosing the acceptable opportunities. The introduction of a classifying system will significantly simplify the process, especially for a large number of continuously updated projects and regularly taken investment decisions. Once trained, the network will be an effortless instrument in the hands of the decision-maker, whenever the information available is subject to change. Second, standard neural networks have been successfully applied to classify takeover targets [17]. Third, there have been already developed soft intelligent trading systems and artificial stock markets [12,32,46,47,48] that will further benefit from the introduction of the multiple modelling-perspective approach. It will power an investment agent to perform preliminary project evaluation and rating, risk analysis and classification of admissible stocks, and trading simulation.

Figure 1 describes the interrelations between financial, soft computing and artificial intelligence techniques, as well as between theoretical and empirical studies. All these approaches are involved into the process of formulating the investment classifier and building the multimodel intelligent system. The organisation of the paper follows a step by step approach, outlining the soft classifier in Section 2, building the multimodel knowledge representation in Section 3, and presenting the empirical results in Section 4. The classifier is introduced by first formulating in subsection 2.1 a fuzzy-valued criteria that is better capable of investment evaluation under uncertain market data than a crisp criteria. Next, in subsection 2.2, the structure of a hybrid fuzzy neural network is identified that is effective in approximating the above criteria. Finally, in subsection 2.3, a genetic algorithm is suggested and a bidirectional incremental evolutionary strategy is developed that is efficient in training the fuzzy network. The second part of the paper ends by stating the advantages of the soft investment classifier. In the third part, a multimodel investment domain is built up including the developed classifier. First, in subsection 3.1, a number of relevant models are referred to and their characteristics are analysed. The models are chosen with the purpose to give the

intelligent system the ability to perform various tasks. From preliminary crisp evaluation of a project, through more informative fuzzy investment appraisal and ranking, going on with project risk and robustness estimation, an agent-dependent risk classification and recommendation of attractive projects, and finally suggesting stock-trading strategies. Next, in subsection 3.2, the position of the models is considered according to several conceptual perspectives as rigidity, resolution, precision, and a multiperspective domain space is constructed. The paper ends with presenting empirical results based on UK companies traded on the London Stock Exchange, and discussing the advantages of the multimodel intelligent system.




Figure 1: Technique interrelations in formulating the investment classifier and building the multiple-model intelligent system
Boxes in bold follow the development of the proposed approach.

2 Soft Classifier

2.1 Fuzzy valued criterion

The need for classical investment model revision and the grounds for new types of models are well recognised. Various modifications [14,45] eliminate only some of the problems associated with the standard criteria and it has been realised that the removal of any of the perfect market assumptions typically destroys the foundations of generally accepted investment-selection techniques. In [45], it is emphasised that having rules which lead to correct decisions in the presence of capital market imperfections would lead to a situation where modern finance theory can be applied consistently. Furthermore, the mathematics underlying the standard financial techniques neglects extreme situations and regards large market shifts as too unlikely to matter. Such techniques may account for what occurs most of the time in the market, but the picture they present does not reflect the reality, as major events happen in the residual time and investors are ‘surprised’ by ‘unexpected’ market movements. It is reasoned in [2] that the perception of concepts inherent or surrounding the investment process, whose character is not principally measurable, is best handled by the soft mathematics emerging from the theory of fuzzy sets. Thus, a fuzzy approach allows for market fluctuations well beyond the probability type of uncertainty permitted by the standard financial methods. It does not impose predefined data or market behaviour, there is only an attempt to model as much uncertainty as the environment can possibly embody, producing better estimates of the investment risk.

Considering the above arguments, we formulate a fuzzy-valued criterion at the first stage of the proposed investment appraisal method. The initial point is the price-dividend relationship, where we consider time-varying stock return. Prices are too volatile to be rational forecasts of future dividends discounted at a constant rate and empirical tests have convinced many financial economists that stock returns are time-varying rather than constant [11]. Allowing time-varying returns transforms the price-dividend relation into nonlinear. If its loglinear approximation is considered, and the resulting equation is solved forward for the log stock price, a price estimation \hat{p}_0 is produced in period $t=0$, (see Appendix A1 for details). Let T be the investment horizon, then a project is profitable when the estimated share price exceeds the market share price $\hat{p}_0 > p_0$ at $t=0$.

Based on this, the fuzzy-valued criterion is formulated following a procedure in four steps. First, for each project, the parameters of linearisation δ and λ are obtained and considered crisp. Second, market uncertainty is introduced to the data covering share prices, dividend yields and returns, applying a specific calibration technique to produce positive nonlinear fuzzy coefficients $\tilde{A}_t, \tilde{B}_t, \tilde{C}_t, 1 \leq t \leq T$. Third, the fuzzy-valued log share price \tilde{P} at $t=0$ is presented as

$$\begin{aligned} \tilde{P}_0 &= \sum_{t=1}^T \lambda^{t-1} \left[(1-\lambda) (\tilde{C}_t d_{y_t} + \tilde{A}_t p_t) + \delta - \tilde{B}_t r_t \right] + \lambda^T \tilde{A}_T p_T = \\ &= \tilde{A}_1 g_{A1} + \dots + \tilde{A}_T g_{AT} - \tilde{B}_1 g_{B1} - \dots - \tilde{B}_T g_{BT} + \dots + \tilde{C}_T g_{CT} + g, \quad 0 < \lambda, \delta < 1, \end{aligned} \quad (1)$$

where all g functions are continuous and defined on the crisp market data employed to evaluate a project. Thus, the fuzzy log share price from [40] is transformed into a continuous multivariable fuzzy-valued function. The modification provides that the fuzzy neural network introduced in the next subsection is capable of approximating \tilde{P}_0 to an arbitrary degree of accuracy. Forth, applying the extension principle, the nonlinear membership function of the solution is obtained. For the specific formulation of \tilde{P}_0 , the α -cut $\Omega_{P_0}(\alpha)$ is equivalent to the interval arithmetic solution. The details of the four-step procedure are described in Appendix A1.

Solving equation (1) identifies the set of estimated log share-price values corresponding to all future log share prices, dividend yields and returns possible at some level of uncertainty, u . This set is situated at the same level u . Therefore, there is a critical level of uncertainty, $u_{project}$, embodied into the market data we use to evaluate a project, and this level delimits the project's investment risk. The risk measure $\alpha_{project}$ below is derived from the membership level $\mu(p_0 / \tilde{P}_0)$ of the market price p_0 to the evaluated fuzzy share price \tilde{P}_0 .

$$\alpha_{project} = \mu(p_0 / \tilde{P}_0) = \sup\{\alpha / y_p = p_0\}, I - u_{project} = \alpha_{project} \in [0, I], \quad (2)$$

The following reasons advocate such risk definition. The lower the critical level of uncertainty at which there is a chance for the project being unprofitable, the higher the investment risk. Furthermore, $\alpha_{project}$ is the membership level of the fuzzy log share price, below and at which the solution includes values smaller or equal to the initial log market price, and above which the project is profitable.

Finally, as the variety of market agents work within diverse risk ranges, the same project will be acceptable for some of them and too risky for others. Thus, an agent-dependent threshold will benefit the decision-maker. In conclusion, the investment criterion is described with

$$\alpha_{project} \leq \alpha_{agent}, \quad (3)$$

where α_{agent} communicates the admissible risk value. Consequently, for a particular agent, a project is worth investing in if the associated risk does not exceed an acceptable level.

2.2 Fuzzy neural network

The second stage of the method consists of building a regular fuzzy neural network, to approximate the continuous multivariable fuzzy-valued function \tilde{P}_0 , and subsequently including two more layers to discriminate between risky projects. The approximating capabilities of regular fuzzy networks have been intensively studied in the last few years. It is demonstrated in [8,9] that such neural nets are not able to represent continuous fuzzy functions to an arbitrary degree of accuracy. On the other hand, [33] proves that they are universal approximator for continuous fuzzy-valued functions.

Let \mathbb{R} is the real number set, and $F_0(\mathbb{R})$ is the set of all fuzzy numbers on \mathbb{R} . Then a continuous fuzzy function F_{fuzzy} is a mapping from and to the fuzzy number set $F_{fuzzy} : F_0(\mathbb{R}) \rightarrow F_0(\mathbb{R})$. A continuous fuzzy-valued function $F_{fuzzy-valued}$, on the other hand, is a projection from the real number set to the set of fuzzy numbers, $F_{fuzzy-valued} : \mathbb{R} \rightarrow F_0(\mathbb{R})$. We have constructed the share price as a function of the second type, as described in the previous subsection.

Based on the theorems proved in [33] about single-variable functions, we formulate four Remarks concerning the multivariable case. Detailed mathematical explanation is given in Appendix A2. Thus a particular class of regular fuzzy networks is identified that are capable of representing multivariable continuous fuzzy-valued functions. The neural net structure includes four layers, with sigmoid transfer functions and shift terms in the first hidden layer, and identity transfer functions with no shift terms in the input, the second hidden and the output layer. In order to reduce the complexity of the network training task without weakening the approximating capabilities of the neural net, the weights and the shift terms are restricted to be real numbers with the exception of the weights to the output layer that are triangular fuzzy numbers.

Figure 2 introduces the network structure classifying investment projects according to the agent-dependent risk criterion (3). The configuration consists of a regular fuzzy neural network part and a hybrid segment. The dashed box outlines the regular module. Its input layer is fed with crisp data - log stock prices p_t , log returns r_t and log dividend yields dy_t - while the output layer produces the nonlinear fuzzy number \tilde{P}_{RFNN} .

$$\tilde{P}_{RFNN}(p_1, \dots, p_T, r_1, \dots, r_T, dy_1, \dots, dy_T) = \sum_{i=1}^q \tilde{V}_i \left(\sum_{j=1}^m e_{ij} \sigma \left(\sum_{\ell=1}^T (w_{j\ell} p_\ell + u_{j\ell} r_\ell + z_{j\ell} dy_\ell) + \theta_j \right) \right) \quad (4)$$

$q, m \in \mathbb{N}, \tilde{V}_i \in F_0(\mathbb{R}), e_{ij}, \theta_j, w_{j\ell}, u_{j\ell}, z_{j\ell} \in \mathbb{R}$,

where $w_{j\ell}$, $u_{j\ell}$, $z_{j\ell}$ and e_{ij} are real weights, θ_j are real shift terms, \tilde{V}_i are triangular fuzzy weights, σ is the sigmoid transfer function, T is the investment horizon, m and q are the




Figure 2: Neural network structure classifying projects with acceptable risk levels

Regular Fuzzy Neural Network is outlined in the dashed box

network size: $(3 * T) \times m \times q \times 1$

T is the investment horizon

m and q are the number of nodes in the first and second hidden layer, respectively

crisp inputs: log stock prices p_t , log returns r_t and log dividend yields dy_t

weights: real numbers $e_{ij}, w_{j\ell}, u_{j\ell}, z_{j\ell}$, and triangular fuzzy numbers \tilde{V}_i

first hidden layer: sigmoid transfer functions σ with real shifts terms θ_j

second hidden layer: identity transfer functions i with no shift terms

nonlinear fuzzy output \tilde{P}_{RFNN} approximating the fuzzy log share price \tilde{P}_0 at $t=0$

Attached Hybrid Part

φ is a transfer function producing an approximation $\alpha_{FNN}^{project}$ of the project's risk $\alpha_{project}$,

based on the regular part output \tilde{P}_{RFNN} and the market price p_0 at $t=0$.

ψ is a hard limit transfer function with an agent-dependent threshold α_{agent}

output = 1 \rightarrow identified acceptable-risk investments (recommendation *buy*)

output = 0 \rightarrow rejected projects as too risky for the concerned market agent (*sell*)

number of nodes in the first and second hidden layer respectively. \tilde{P}_{RFNN} is an approximation of the estimated fuzzy log price \tilde{P}_0 , and is illustrated with its membership function in the network diagram below. The extension principle and the interval arithmetic evaluation of such fuzzy networks are equivalent and the α -cuts of the output \tilde{P}_{RFNN} are computed as in Appendix A2. The hybrid part includes two nodes with transfer functions φ and ψ , correspondingly. The first node produces the investment risk $\alpha_{FNN}^{project}$ relevant to the evaluated share price \tilde{P}_{RFNN} and the market price p_0 at $t=0$. Thus φ is described with

$$\alpha_{FNN}^{project} = \varphi(\tilde{P}_{FNN}, p_0) = \mu(p_0 / \tilde{P}_{FNN}) = \sup\{\alpha / y_{P_{FNN}} = p_0\}, \quad (5)$$

where μ is the nonlinear membership function of \tilde{P}_{RFNN} , $\mu(p_0 / \tilde{P}_{FNN})$ is the level of membership of p_0 to \tilde{P}_{RFNN} , and $\alpha_{FNN}^{project}$ can take any value in the closed interval $[0,1]$.

Finally, $\psi\left(\alpha_{FNN}^{project}, \alpha_{agent}\right)$ is a hard limit transfer function comparing the evaluated risk level of the investment project under consideration and the acceptable risk level α_{agent} of the concerned market agent. The tolerable risk α_{agent} can take any value in the open interval $(0,1)$ and act as a threshold in ψ . As a result, only projects that are admissible for the particular investment agent will be recommended with a network outcome of I , and the rest of the projects will be rejected producing 0 that indicates they are quite risky to be considered as investment opportunities. Each agent can also revise the threshold to suit his current position. Thus, it is recognised that the same project will have different bearings on the risk position of various market players and their particular circumstances at that time. Such differentiation suggests that if we consider the outcomes of I and 0 as recommendations to buy and sell, then the advice is also agent-dependent. This is a distinctive feature of the method in comparison with the general practice of project-related only recommendation.

2.3 Bidirectional incremental evolution

At the next stage of the developed technique, the regular part of the fuzzy network in Figure 2 is trained to approximate the fuzzy log share price \tilde{P}_0 , using a genetic algorithm and following a bidirectional incremental evolutionary strategy. The genetic algorithm is specified with its initialisation, selection and recombination operators. The initialisation step includes chromosome encoding and generating the first population. Let a triangular fuzzy weight \tilde{V}_i be presented with three real numbers (v_i^a, v_i^b, v_i^c) corresponding to its support and vertex. Then the relations $v_i^a < v_i^b < v_i^c$, $1 \leq i \leq q$, are valid. Thus the neural net can be coded into a chromosome χ of size $M = 3mT + m + qm + 3q$, where M is equal to the number of real weights and shift terms plus three times the number of fuzzy weights in the network. The initial population X of s individuals χ is generated simultaneously as a matrix of size $M \times s$. The elements of X are realisations of a random variable with standard normal distribution. A block representation of X helps to concurrently sort its elements according to the inequality restrictions above. Next, a breeding subpopulation X_{SUB} is selected, which consists of the s_l best-fitted chromosomes, where $s_l < s$. The selection is based on the fitness function f_ξ ,

$$f_{\xi} = \begin{cases} 0, & \xi > \xi_A \\ (\xi_A - \xi) * \xi_B, & \xi \leq \xi_A \end{cases}, \quad (6)$$

where ξ_A and ξ_B are parameters related to the approximating precision of the coded network, and ξ represents the error of the fuzzy network for the corresponding chromosome. Consequently,

$$\xi = \max_{\alpha \in \{0, 0.1, \dots, 1\}} \left(\max \left(\left| P_0(\alpha) - P_{RFNN}(\alpha) \right|, \left| \overline{P_0(\alpha)} - \overline{P_{RFNN}(\alpha)} \right| \right) \right), \quad (7)$$

where $\left[\underline{P_{RFNN}(\alpha)}, \overline{P_{RFNN}(\alpha)} \right]$ and $\left[\underline{P_0(\alpha)}, \overline{P_0(\alpha)} \right]$ are the α -cuts of the output \tilde{P}_{RFNN} and the share price \tilde{P}_0 , correspondingly. Thus the best subpopulation X_{SUB} is identified, and on its basis the recombination process finally builds the new generation X_{NEW} . A multipoint crossover operator is applied on X_{SUB} to produce a temporary full-size population X_{TEMP} . The number and position of crossover points is randomly chosen every generation. A real-number network parameter is recognised as a gene within the chromosome, and a triplet representing a fuzzy-number parameter is also considered as a single gene. Then crossover points are only set between genes. Randomly chosen chromosomes from X_{SUB} are combined as in Figure 3 to obtain two offspring, only one of which is included in X_{TEMP} .




Figure 3: Multipoint crossover operator

The crossover points are only set between genes. A single gene consists either of one real-number network parameter or of a triplet representing a fuzzy-number weight. The parent chromosomes belong to the best subpopulation X_{SUB} . Only the first-child chromosome is added to X_{SUB} to form the temporary full-size population X_{TEMP} .

The mutation operator concludes the recombination step, transforming the temporary population into the new generation of fuzzy-network representations. This step involves a constant mutation rate τ , where $0 < \tau < 0.2$. Thus the number of mutated genes is constant $\tau * (3mT + m + qm + q)$, but their place in the chromosome is randomly chosen every generation. Modified elements are generated as realisations of a random variable with standard normal distribution. All the mutated triplet genes are concurrently sorted according to the inequality restrictions above.

This genetic algorithm is applied within a bidirectional incremental evolutionary strategy, suggested on the following grounds. A complex task is difficult to evolve, as it is not possible to directly discover a general solution. The stalling effect in direct evolution may be defeated by implementing incremental strategies, where neural networks learn complex behaviour while starting with simple functioning and gradually increasing the complexity of the task [18,21]. The problem is that the relevant subset of simple tasks as well as their sequence is not uniformly defined, and so is an incremental strategy. Consequently, it is appropriate to

identify the efficient subset of tasks and their efficient sequence [24]. Bidirectional incremental evolution applied here deals with the question of efficiency by first identifying the subtasks and their sequence, then evolving them separately, and finally merging the tasks gradually while following the efficient sequence. When the investment paradigm is considered, the domain of subtasks is described as follows. If T is the investment horizon, N_1 is the number of periods in which projects are available, $\Delta t_1 = [t_{01}, t_{01} + T], \dots, \Delta t_{N_1} = [t_{0N_1}, t_{0N_1} + T]$, and N_2 is the number of companies, then there are $N = N_1 * N_2$ single-company single-period projects constituting the first level of subtasks with lowest complexity. The next levels involve increasing number of single projects. They may concern the same company over several periods or the same type of companies over one or a number of periods, or may include different types of companies. According to its investment risk, there exist three modes of a single project. It can be profitable and not risky when $\alpha_{project} = 0$, risky for $0 < \alpha_{project} < 1$, or too risky and unprofitable when $\alpha_{project} = 1$. There are also five types of companies. Those with investment risk 0 over all the periods are quite rare, having in mind that the market is modelled as highly uncertain. The other types include companies with continuously improving levels of risk, and companies with unstable risk levels $0 \leq \alpha_{project} \leq 1$ without a particular direction. Finally, those with constantly worsening investment risk, and the ones with $\alpha_{project} = 1$ over all periods. Providing the training set includes companies of all types and single projects covering the three important modes of $\alpha_{project}$, then the evolved regular fuzzy neural network will sufficiently predict the fuzzy log share price \tilde{P}_0 of new investment opportunities.

The overall idea of the evolutionary strategy is presented below, while detailed description is provided in Appendix A3. The fitness function applied throughout the evolution is f_ξ from definition (6), while the objective function is dynamic and is updated at each step of the strategy. First a random initial population of size s is generated and a fuzzy network is evolved over the full set of single projects for a probing number of generations N_{gen} using f_ξ . Then, if the objective, based on the average value of the error ξ over the resulting

subpopulation of s_1 best-fitted chromosomes, is above a test limit $\frac{1}{s_1} \sum_{i=1}^{s_1} \max_n(\xi(\chi_i)) > \xi_{DEC1}$,

the evolution starts again with a new random initial population. Otherwise the single projects are probed with an updated objective function over the best subpopulation. If there does not exist a single project with an objective value below an updated test limit, then a new full-size population is generated by recombination of the best subpopulation and the evolution is continued for another N_{gen} iterations. Otherwise, the projects satisfying the condition are probed again opposite the second limit to identify project sets of maximum size rather than single projects with a satisfying combined objective value. Then the full training set n is partitioned into subsets $n = \{n_{11}, \dots, n_{1j}, \dots, n_{1j}, n_2\}$, where J is the number of subsets of projects satisfying the second limit, and n_2 is the subset of single projects that do not satisfy the condition. This is the first decomposition level of the training set. Now $J + 1$ different full-size populations are generated by recombination of the same breeding subpopulation and a separate fuzzy network is evolved in N_{gen} generations for each training subset of n . Then the steps up to here, with revised objective functions, are repeated for each training subset. Thus several levels of decomposition of the training set are identified, and each level is characterised with a unique partitioning into subsets and a specific number J . The decomposition stage of the evolutionary strategy completes when the neural networks evolved over each training subset reaches an average value of the error over the first half of the best subpopulation below a test limit ξ_{DECEND} . Then, the incremental part of the evolution starts

from the highest decomposition level. Each of the training subsets at this level has an evolved best subpopulation associated with it. A full-size population is generated by recombination based on all subpopulations. The evolution continues over the whole training set existing at the highest decomposition step until a revised objective function gets below ξ_{INC} . This is the first incremental step. Then the second highest decomposition level is considered. The training set existing at this level includes by definition the whole training set from the highest decomposition step and some further subsets of projects. Again one full-size population is generated by recombination of the breeding subpopulations associated with each training subset here. The subset equivalent to the highest decomposition set of projects is presented with the best subpopulation evolved at the first incremental level. The objective limit is again ξ_{INC} but the objective function includes more projects. This is the second incremental level. The procedure continues by analogy until the first decomposition step is reached, where the partitioning was applied over the initial full training set. It will be the final incremental level. A neural network is evolved until the error of one chromosome only, rather than over a subpopulation of chromosomes, but including all the projects, falls below ξ_{INCEND} where $\xi_{INCEND} < \xi_{INC}$. This best chromosome χ_{INCEND}^{best} represents the completely evolved regular fuzzy neural network.

Figure 4 above represents the evolutionary strategy. For simplicity, the decomposition part is slightly generalised in the diagram omitting the test limits $\xi_{DEC4}^{(k)}$, (see Appendix A3). The bidirectional incremental algorithm implements a dynamic objective function. Its fitness function f_{ξ} , on the other hand, will be the same over all steps, and equal to the one used in direct evolution, for an easy comparison of the results.

2.4 Conclusions

In conclusion, the advantages of the developed method cover the following aspects. The investment classifier is based on a fuzzy-valued criterion that better handles uncertain market data than crisp criteria [11]. Whatever reason one has for modifying the classic result [14,45], the allowances provided by the fuzzy-valued criterion will cover these specific circumstances and will include the modified value, as well as other possible values, increasing the flexibility of the involved calculations. Moreover, a measure for the risk associated with each project is suggested, thus providing grounds for an alternative investment ranking. This result emphasises the method as more informative to the decision-maker, in comparison with other fuzzy approaches [5,6,10,30]. Next, a fuzzy neural network structure is identified capable of approximating the multivariable criteria. The configuration is derived by developing further the result for single-variable fuzzy-valued functions from [33]. Then, a genetic algorithm is suggested for optimising the parameters of the network. Starting with a procedure from [8] for a simple network configuration, and recursively testing it on and modifying it for the more complex structure from Figure 2, the algorithm is developed to demonstrate increased speed and efficiency. Finally, a bidirectional incremental evolutionary strategy is outlined that is particularly effective in training fuzzy networks with a larger number of nodes and layers. Direct evolution fails to solve the task. We can compare our empirical results (see subsection 4.1) with other applications of genetic algorithms to optimising fuzzy network parameters. In [8] quite a simpler structure is trained, with direct evolution only, to approximate an elementary single-variable fuzzy function.

Optimising the classifier is time-consuming and the complexity of the task increases with expanding the investment horizon. Still, it is not a disadvantage of the method, as the model is only incorporated into the intelligent system after training, and then instantly provides support to the decision-maker. Moreover, several soft classifiers can be included into the multimodel based system (see Section 3), each trained to give recommendation over different horizon-length. Another beneficial feature is the agent-dependent recommendation. Rather than providing an abstract advice, the model relates every investment project to the possible circumstances or preferences of each major type of market agents.

3 Multimodel knowledge representation

3.1 Model selection

The financial techniques to be incorporated into the multimodel domain are chosen with the purpose to give the intelligent system the ability to support a decision-maker through various investment inquiries. Starting with a share-price estimation based on the log-linearisation of the price-dividend relation which is solved forward over the project length [11]. This will provide a preliminary project evaluation, handling time-varying returns. If the estimated figure encouragingly diverges positively from the market price, further investigation can be undertaken. A slightly more flexible criterion will be employed to tackle the timing of the initial outlay. It is shown in [14] that if the value of the project at the time it is evaluated is stochastically fluctuating and depending on a random start time, then there exists a trade-off between a larger versus a later net benefit. Thus the optimal timing of buying the shares will be identified, taking into account investment irreversibility. The best start period equals the time at which the benefit reaches a threshold. In comparison, if the standard criterion were used, then the agent would invest sooner but rely on larger rates to get the same profit.

Up until now the decision-maker has an idea which projects could be beneficial and is intent to get more reliable evaluation. Although with increasing flexibility in comparison with standard investment criteria, all models above are crisp and therefore working under relatively narrow presumptions about the underlying distributions and market behaviour. Next some fuzzy criteria will be introduced into the multimodel domain that are effective under a high level and diverse forms of uncertainty, i.e. market imperfections, absence of complete or precise data, and presence of human involvement in price formation. In [5] an evaluation technique is suggested that can be applied here in the following aspect. Using the standard arithmetic of fuzzy numbers, and modelling uncertain amounts in the project cashflow as well as the estimated rate with nonlinear trapezium membership functions, two different formulae are applied when an amount is positive or negative. For example, if the project involves buying shares in the beginning and selling them in the end, the first formula will be only relevant. If the project prescribes various optimal points in time for buying and selling different shares, then the two formulae will be involved. Other fuzzy models extend even further the flexibility of the evaluation technique. In [10], the option of associating a different rate to each amount is offered. The main contribution in [30] consists in fuzzifying the project duration over the relevant time periods. Usually fuzzified duration is presented as a discrete fuzzy set with a membership function defined by a collection of positive integers each corresponding to the end of a time period according to the accepted time division, e.g. months, weeks, days. Alternatively in [30], the duration is a real fuzzy number allowing for the project to finish at any moment, not only at the end of a time period, i.e. in the middle of the month or throughout the week. Finally, among this group of fuzzy criteria mainly based on the stock-price evaluation, the technique from [36] finds its place. There, a hybrid network is developed and a fuzzy membership array is embedded into a neural network. Although the approach is applied to predicting a stock index, it effectively can be used in single-asset or portfolio price evaluation. The out-of-sample forecasts of the hybrid net up to 24 months ahead without updating the model are compared with these of several crisp regressions and the neuro-fuzzy model is found to perform substantially better.

The next group of models will present the decision-maker with still reliable but further progressively informative solutions, comparing with the above techniques. Questions considered include fuzzy ranking, investment risk evaluation, measuring project robustness towards market uncertainty, and agent-dependent classification of attractive projects. Using a procedure suggested in [5], the projects can be ranked according to the evaluated membership functions for the fuzzy criterion. Further in [23,43], a risk measure is proposed and an alternative risk-based ranking technique is described. The solution procedure there involves a multiple interval analysis, which enables investors to consider a project and take decisions based on varying levels of uncertainty. Increasing the range of uncertainty modelled into the fuzzy data, one can determine the robustness of the investment risk associated with each

project , as in [40,42]. Thus the ranking technique is refined and based on both the projects' risk and robustness evaluation. Analogous risk measure is used in [41] and in Section 2 here, when building the soft classifier. Several such fuzzy networks can be included into the multimodel intelligent system, each network trained over projects with different duration. All the classifiers will be trained prior to entering the system, and ready to provide agent-dependent recommendation. The classifying model can go one step further by incorporating into the neural network structure the robustness measure as well. Thus there will be agent-dependent thresholds for both investment risk and project robustness, following the intuition that projects with a small and a highly robust investment risk are preferable. Consequently, the fuzzy criterion evolves into a considerably informative method.

Table 1: Selected models for the multiperspective intelligent system

<i>models</i>	<i>characteristics</i>	<i>major</i>
log-linearised price evaluation [11]	Good for preliminary project evaluation. Handles time-varying rates. Slightly increased flexibility and accuracy, in comparison with standard investment criteria.	<i>preliminary evaluation, crisp criteria</i>
optimal rules for irreversible investment [14]	Helps identify the optimal time of buying the assets, considering investment irreversibility and a benefit threshold. Increased flexibility in handling market data. A crisp criterion.	
fuzzy present value [5]	Increased reliability in market evaluation. A fuzzy criterion.	<i>reliable</i>
generalised fuzzy criterion [10]	Allows a different rate to be associated with each amount in the project cashflow.	<i>evaluation, fuzzy or soft</i>
generalised fuzzy criterion [30]	Provides alternative fuzzification of the project duration.	
neuro-fuzzy price evaluation [36]	Exploits financial market inefficiencies and extracts nonlinear patterns that even sophisticated econometric models can not cope with. Combines fuzzy logic with a neural network.	<i>techniques</i>
fuzzy ranking [5]	Suggests a technique for ranking fuzzy numbers and considers the membership functions of projects' fuzzy present value.	<i>informative ranking and classification, fuzzy and soft techniques</i>
investment risk evaluation [23,43]	Applies α -cut arithmetic in fuzzy price evaluation, instead of standard fuzzy arithmetic. Derives an investment risk measure and ranks the projects accordingly.	
project robustness evaluation [40,42]	Uses two calibration procedures when fuzzifying the market data, thus modelling an increased range of uncertainty. Identifies which projects are more robust based on the change in the investment risk measure under varying data calibration. Suggests an alternative ranking using both the risk and robustness measures.	
classifying low-risk projects [41,manuscript]	Develops a genetic algorithm and a bidirectional evolutionary strategy to train a fuzzy neural network to classify stock projects according to the investment risk measure and an agent-dependent threshold.	
classifying highly-robust projects [future rresearch]	Will incorporate the measure of the project robustness into the soft-classifying model, following the heuristic that low-risk and highly-robust projects are preferable.	
portfolio selection [46]	Investment expert knowledge is reflected into the stock return possibility or fuzzy probability distributions. Selection is based on minimising corresponding parameters in the portfolio distribution.	<i>portfolio selection and</i>
dynamic portfolio management [35]	Manages an optimal stock portfolio in a fuzzy dynamic environment by solving a fuzzy linear tracking problem.	
trading model [32]	Integrates neural nets and fuzzy Delphi methods. An effective trading approach without and under transaction costs.	<i>stock trading, soft or hybrid techniques</i>
trading model [22]	A genetic-fuzzy model for discovering trading knowledge.	
artificial stock market [12]	An agent-based artificial stock market evolving successful traders.	
artificial stock market [47]	Suggests that the agents have the ability to compress numerous crisp trading rules and conditions into a few fuzzy notions and analyse them using fuzzy logic.	<i>techniques</i>

The final set of models suggests portfolio-selection and stock-trading strategies. In [46], two portfolio selection models are proposed where investment expert knowledge is reflected into the fuzzy probability or possibility distributions of stock returns. Distributions are obtained depending on stock possibility grades offered by experts. The aim is to minimise the variance of the fuzzy probability distribution or to minimise the spread of the possibility distribution of the return on the portfolio. Further in [35], a dynamic portfolio selection is outlined. A fuzzy control model is used to manage a portfolio in a fuzzy dynamic environment in the presence of financial constraints. One riskless and n risky assets are employed, modelling the factor imprecision with fuzzy sets. A fuzzy linear tracking problem is solved using the Kalman filter. Next, the effort in [32] is to develop a stock-trading system, integrating neural nets and fuzzy Delphi methods. The result shows that without and under transaction costs the integrated model outperforms the single neural network. Although the genetic-fuzzy model in [22] is applied to currency trading, no further adjustment is necessary to use it in stock trading, as the techniques has all the features to cope with the problem efficiently. The approach provides an automated method for discovering trading knowledge. Finally, an architecture for an artificial stock market is suggested in [12] that is agent-based and includes evolving successful traders. In [47] another artificial stock market model is introduced. It is proved there that similar results can be obtained, either considering traders capable of handling a large number of rules with numerous conditions, or allowing the reasoning process to be severely limited. In the latter case the results are even improved. This case is also closer to reality, and agents have the ability to compress information into a few fuzzy notions that they can process and analyse with fuzzy logic. All selected models are included in Table 1. The system is still open for more models, but each choice should be justified.

3.2 Building the multiperspective model space

A multimodel investment domain will help the decision-maker with the process of multiperspective analysis and multilevel reasoning. Being exposed to a variety of possible interpretations, will effortlessly enriches his vocabulary of relationships and enlarges his search space for hypothesis construction. He will be able to look at the investment problem from various angles thus improving his ability to understand and solve specific queries.

Building the multimodel space starts with choosing the modelling dimensions [26,27,28,29]. This is the set of properties that represents fundamental characteristics associated with the context or framing of the investment problem. Each dimension - i.e. scope, resolution, rigidity - denotes a different context, which directs the multiperspective reasoning. For example, scope is concerned with the extent of the problem being modelled. We may simply want to evaluate a project. Broadening the scope, an optimal portfolio can be identified. Finally, the functioning of an artificial stock market may be under question. Further, resolution dictates how much detail is included in a model. As an illustration, the factor analysis when managing a dynamic portfolio may be based on a few major determinants only. Increasing the resolution, some minor factors will be included, or the major determinants can be decomposed into several smaller ones and their effect studied separately. When rigidity is considered, we focus on the ability of the model to handle uncertain data and real-market situations. In this sense, the crisp models are most rigid, and progressing along the fuzzy and soft techniques, the hybrid approaches are most flexible.

The multimodel space can be visualised as a geometrical shape with several axes or dimensions. It is easier to think of a cubical form and Figure 5 presents the three dimensions described above: scope, resolution and rigidity. In practice, there are more perspectives and each component cube explodes into another cubical structure. This time axes are different, e.g. generality, precision and accuracy, and provide support for considering additional aspects of context. By choosing a value for every dimension, one can navigate to a specific model in the multiple structure. Neighbouring models differ only slightly, i.e. two soft classifiers recommending projects over different investment horizon. Distantly related techniques, on the other hand, are quite unlike.




Figure 5: Multiple model structure
Each component cube comprises smaller cubes.

This approach to knowledge representation produces a domain structure with a valuable inherent quality. The multimodel space provides enhanced flexibility in problem solving. For example, a lower-resolution technique will be sufficient in one situation, while a larger-scope model will be required in another, and a less rigid method in yet another case. Thus positions on each of the modelling dimensions will be associated with the demands of a particular investment problem. Moreover, changing models is beneficial practice in seeking alternatives during the solution process. For instance, moving from an artificial stock market with numerous crisp trading rules and conditions to a market model with only a few efficient fuzzy rules, can provide an improved solution to the initial problem, and help the market agent better reason about the result. Further, the multimodel approach also caters for the dynamic knowledge immanent in the interaction between different models. To illustrate, the decision-maker may not just look for the answer to a single question, but rather work out the result of a set of problems, or test an investment strategy involving several models. Navigating through the model space, this challenge is comfortably met.

4 Empirical results and conclusions

4.1 Empirical results

The empirical data involve three UK companies - Goodwin, Dixons Group and Marks&Spencer - over the period from June 1998 to December 1999. They are chosen from a database of 35 firms to represent three major types of company behaviour. In Figure 6, the fuzzy log-dividend time-trajectory related to each firm illustrates modelled market uncertainty. Furthermore, a six-month investment horizon is selected, producing three projects per company and nine in total. This set of projects is divided into three subsets, used correspondingly for training, testing and predicting with the fuzzy neural network. Table 2 introduces the division of the data set and the accepted project notation. Table 3 presents the risk level for each project evaluated with the fuzzy criteria.




Figure 6a: Goodwin
Fuzzy log-dividend: July'98–Dec'99.




Figure 6b: Dixons Group
Fuzzy log-dividend: July'98–Dec'99.




Figure 6c: Marks&Spencer
Fuzzy log-dividend: July'98–Dec'99.




Figure 7: Investment risk $\alpha_{project} = 0.858$
Project 9: Dixons Group, July–Dec'99.

Table 2: Data division

<i>period / company</i>	<i>Goodwin</i>	<i>Dixons Group</i>	<i>Marks&Spencer</i>
July-December, 1998	Project 1: training	Project 3: training	Project 5: training
January-June, 1999	Project 2: training	Project 4: training	Project 6: training
July-December, 1999	Project 7: testing	Project 9: predicting	Project 8: testing

Table 3: Investment risk evaluation

<i>period / company</i>	<i>Goodwin</i>	<i>Dixons Group</i>	<i>Marks&Spencer</i>
	<i>project: risk $\alpha_{project}$</i>	<i>project: risk $\alpha_{project}$</i>	<i>project: risk $\alpha_{project}$</i>
July-December, 1998	Project 1: 1	Project 3: 1	Project 5: 1
January-June, 1999	Project 2: 0.683	Project 4: 0	Project 6: 1
July-December, 1999	Project 7: 0	Project 9: 0.858	Project 8: 1

In the second column of Table 3, Goodwin demonstrates a continuously improving risk measure, reaching $\alpha_{project} = 0$ for project 7. In the third column, Dixons Group indicates oscillating levels $0 \leq \alpha_{project} \leq 1$, without a particular direction over the related projects. Finally, Marks&Spencer exhibits the highest risk level $\alpha_{project} = 1$ all over. Thus, it is provided that three major types of companies are represented. It is also guaranteed that the training set includes single projects covering the three important risk modes: $\alpha_{project} = 0$ (project 4), the open interval $0 < \alpha_{project} < 1$ (project 2), and $\alpha_{project} = 1$ (projects 1,3,5 and 6).

Figure 7 illustrates how the risk measure for a project is derived based on the estimated fuzzy-valued log share price \tilde{P}_0 and the market price p_0 .

Next, the genetic algorithm and the bidirectional incremental evolutionary strategy from subsection 2.3 are applied to train the regular fuzzy network module to approximate the fuzzy-valued log share price over the training set, project 1 to project 6. Each project comprises six-month data on log share prices, returns and dividend yields. Consequently, the number of nodes in the input layer of the network is $3T = 3 * 6 = 18$. Then experimenting with several network structures and considering the trade-off between a simpler configuration and evolution convergence, the values $m = 5$ and $q = 3$ are selected, for the number of nodes in the first and second hidden layer correspondingly. Detailed results for each step of the evolutionary strategy from Appendix A3 are provided in Appendix A4. Here, only the major conclusions are discussed. The strategy involves a decomposition and an incremental part. During the decomposition part, the problem is accordingly divided into subtasks of decreasing complexity by partitioning the training set of projects at several levels. Figure 8 presents the identified partitioning. Then the subtasks are merged incrementally in reverse direction.




Figure 8: Training-set partitioning and increment during bidirectional incremental evolution

Decomposition part: the training set is partitioned at several levels, evolving the fuzzy network towards tasks with decreasing complexity.

Incremental part: the training subsets are merged incrementally in reverse direction, evolving the network towards solving the integral problem.

A dynamic objective function is applied at each decomposition and incremental level.

The number of levels and the partitioning at each level is unique to every simulation of the bidirectional strategy. Consequently, it is not possible to average the performance of the strategy over several simulations, as the fitness function trajectory over the generations will go through different training subsets addressed at different times. On the other hand, direct evolution is easily averaged. For more representative comparison, Figure 9 presents a simulation of bidirectional incremental evolution against the averaged result from five direct-evolution simulations. Maximum fitness per generation is presented for each strategy. The bidirectional strategy evolves a fully functional fuzzy network in 148,243 generations. Direct evolution reaches only 46.33% maximum fitness in 500,000 generations. Thus, the empirical results prove decisively the efficiency of the developed evolutionary strategy.




Figure 5: Performance of bidirectional incremental evolution and direct evolution in maximum fitness per generation
Black line: bidirectional incremental evolution advances through several decomposition and incremental tasks and solves the general problem in 148,243 generations.
Lighter line: direct evolution makes some initial progress and then stalls.

Once the regular fuzzy network module is optimised over the training set, it is applied to the test set, project 7 and project 8 (see Table 2). Thus, the out-of-sample performance of the module is examined in approximating the fuzzy-valued log share price. The error ξ from definition (7) is applied to measure the divergence of \tilde{P}_{RFNN} from \tilde{P}_0 , and consequently the performance of the module. The test results, provided in Table 4, corresponds to quite satisfactory approximating capabilities. Consequently, we can use now the hybrid network over the predicting subset, project 9, to estimate the investment risk. In Table 5, the predicted risk value approaches the true value from Figure 7.

Table 4: Test results for the regular fuzzy network module (RFNN)

<i>period / company</i>	<i>Goodwin</i> <i>project: RFNN error ξ</i>	<i>Marks&Spencer</i> <i>project: RFNN error ξ</i>
July-December, 1999	Project 7: 0.0091 < 0.01	Project 8: 0.0024 < 0.01

Table 5: Predicting investment risk with the hybrid fuzzy network

<i>period / company</i>	<i>Dixons Group</i> <i>project: predicted risk $\alpha_{FNN}^{project}$</i>	<i>Dixons Group</i> <i>project: true risk $\alpha_{project}$</i>
July-December, 1999	Project 9: 0.88	Project 9: 0.858

Finally, if the agent-dependent threshold is at 0.9 risk level, than the project will be accepted. On the other hand, if the limit is at 0.8, then this asset will be rejected over the related investment horizon.

4.2 Conclusions

A soft classifier has been constructed that recommends projects according to their evaluated risk and an agent-dependent threshold for the acceptable risk levels. The model is developed in three stages. First, an alternative investment criterion is formulated, including a fuzzy-valued share price estimate. The approach is more reliable than analogous crisp techniques, as it is derived allowing market fluctuations well beyond the probability type of uncertainty permitted by standard financial methods. The criterion is also more informative in comparison with other fuzzy approaches, as it further suggests an investment risk measure. The second stage in the soft model development involves identifying a fuzzy network structure capable of approximating the criterion formulated at stage one. Building on previous studies of fuzzy network approximating qualities concerning simple fuzzy functions or single-variable fuzzy-valued functions, we deduce a structure adequate for the multivariable criterion. The final stage focuses on training the network. A genetic training algorithm is developed that demonstrates high speed and efficiency. Then, an effective bidirectional evolutionary strategy is elaborated, as direct evolution fails to reach a solution to the complex problem of optimising the weights and shift terms in the fuzzy network over a set of investment projects. The strategy involves a decomposition and an incremental part. The integral problem is first divided into subtasks of decreasing complexity by partitioning accordingly the training set of projects. Then the subtasks are merged incrementally to optimise the integral solution.

We next explain how the classifier, once developed and trained, can be used in problem solving. It will be incorporated into a multimodel domain knowledge structure that is to be the expert module in an intelligent system. Building the system includes three stages. First, relevant models are selected to give the environment the ability to generate answers to a variety of queries with increasing complexity. From single-project evaluation, through ranking and agent-dependent risk-classification of available stocks, up to trading recommendation and market simulation. In addition to addressing various though related investment questions, the models have different mathematical grounds. From crisp, through fuzzy and soft computing techniques, up to artificial intelligence and hybrid methods. Thus the same problem can be solved using more or less rigid mathematical approaches. Furthermore, in each model the number of parameters may be reduced or increased according to the nature of the inquiry. The second stage in building the multiple expert structure of the system concerns the identification of major contextual perspectives. We have recognised the dimensions of scope, resolution, rigidity, generality, precision, and accuracy. All models are arranged along these axes, creating a cubical structure where each three-dimensional component explodes into a secondary cubical structure, thus accommodating all six dimensions. So constructed, the multimodel domain facilitates a multiperspective analysis of a single problem. It further provides a powerful environment, in comparison with mono-model based intelligent systems, for solving a variety of problems rather than one particular query. Finally, investment strategies can be tested that involve an ordered set of queries and require a decision at each step. Navigating through the model space, the optimal solution trajectory will be drawn. The third stage in developing the environment is the software design of an intelligent-agent architecture for the system, where the multimodel expert module is incorporated. This step is not addressed here, but the work on it is in progress. In [25], ideas on object-oriented patterns for model-based reasoning are presented that are particularly suitable for designing the multimodel domain, and in [4] an intelligent-agent architecture is described for a system based on such expert module. One further quality of the multimodel based system is the flexibility it can provide in diagnosing user behaviour in order to provide a better decision support, and this is a topic for future research.

Acknowledgements

This work was partly supported by the Nuffield Foundation and by the Engineering and Physical Sciences Research Council Grant GR/R51346/01.

References

- [1] Alexander, G., Sharpe, W., and Bailey, J. (2000). *Fundamentals of Investments*. US Imports & PHIPES.
- [2] Aluja, J. (1996). Towards a New Paradigm of Investment Selection in Uncertainty. *Fuzzy Sets and Systems* vol. 84, 187-197.
- [3] Baeck, T., Fogel, D., and Michalewicz, Z. (2000). *Evolutionary Computation 2: Advanced Algorithms and Operators*. Institute of Physics Publishing.
- [4] Brown, K., Taylor, N., Jing, Y., and Khan, T. (2002). Intelligent Agents: An Approach to Supporting Multiple Model-based Training Systems, in *Proceedings of the International Workshop on Model-based Systems and Qualitative Reasoning for Intelligent Tutoring Systems* at ITS2002, 25-31.
- [5] Buckley, J. (1987). The Fuzzy Mathematics of Finance. *Fuzzy Sets and Systems* vol. 21, 257-273.
- [6] Buckley, J. (1992). Solving Fuzzy Equations in Economics and Finance. *Fuzzy Sets and Systems* vol. 48, 289-296.
- [7] Buckley, J., Eslami, E., and Hayashi, Y. (1997). Solving Fuzzy Equations Using Neural Nets. *Fuzzy Sets and Systems* vol. 86, 271-278.
- [8] Buckley, J. and Feuring, T. (1999). *Fuzzy and Neural: Interactions and Applications*. Physica-Verlag.
- [9] Buckley, J. and Hayashi, Y. (1994). Can Fuzzy Neural Nets Approximate Continuous Fuzzy Functions. *Fuzzy Sets and Systems* vol. 61, 323-330.
- [10] LiCalzi, M. (1990). Towards a General Setting for the Fuzzy Mathematics of Finance. *Fuzzy Sets and Systems* vol. 35, 281-293.
- [11] Campbell, J., Lo, A., and MacKinlay, A. (1997). *The Econometrics of Financial Markets*. Princeton University Press.
- [12] Chen, S.-H., and Yeh, C.-H. (2001). Evolving Traders and the Business School with Genetic Programming: A New Architecture of the Agent-based Artificial Stock Market. *Journal of Economic Dynamics and Control* vol. 25, 363-393.
- [13] Cordon, O., Herrera, F., Hoffmann, F., and Magdalena, L. (2001). *Genetic Fuzzy Systems – Evolutionary Tuning and Learning of Fuzzy Knowledge Bases*. World Scientific.
- [14] Dixit, A., Pindyck, R., and Sodal, S. (1997). A Markup Interpretation of Optimal Rules for Irreversible Investment. *National Bureau of Economic Research Working Papers* vol. 5971.
- [15] Dubois, D., and Prade, H. (2000). *Fundamentals of Fuzzy Sets*. Kluwer Academic. [35]
- [16] Fabozzi, F., and Markowitz, H., eds. (2002). *The theory and Practice of Investment Management*. Wiley.
- [17] Fairclough, D. and Hunter, J. (1998). The Ex-ante Classification of Takeover Targets Using Neural Networks, in *Decision Technologies for Computational Finance*, (Refenes, A.-P., and Moody, J., eds.). Kluwer Academic.
- [18] Filliat, D., Kodjabachian, J., and Meyer, J. (1999). Incremental Evolution of Neural Controllers for Navigation in a 6-legged Robot, in *Proceedings of the Fourth International Symposium on Artificial Life and Robots*, (Sugisaka and Tanaka, eds.). Oita University Press.
- [19] Fogel, D. (1999). *Evolutionary Computation*. Wiley.
- [20] Forbus, K., and de Kleer, J., (1994). *Building Problem Solvers*. MIT Press.
- [21] Gomez, F. and Miikkulainen, R. (1997). Incremental Evolution of Complex General Behaviour. *Adaptive Behaviour* vol. 5, 317-342.
- [22] Goonatillake, S., Campbell, J., and Ahmad, N. (1995). Genetic-Fuzzy Hybrid Systems for Financial Decision Making, in *Advances in Fuzzy Logic, Neural Networks and Genetic Algorithms. Lecture Notes in Artificial Intelligence*, (Furuhashi, T., ed.). Springer-Verlag.
- [23] Hunter, J. and Serguieva, A. (2000). Project Risk Evaluation Using an Alternative to the Standard Present Value Criteria. *Neural Network World* vol. 10, 157-172.

- [24] Kalganova, T. (2000). Bidirectional Incremental Evolution in Extrinsic Evolvable Hardware, in *Proceedings of the Second NASA/DoD Workshop on Evolvable Hardware*, (John, J., and Stoica, A., et al, eds.). 65-74.
- [25] Khan, T. (2002). Object-oriented Patterns for Model-based Reasoning, in *Proceedings of the International Workshop on Model-based Systems and Qualitative Reasoning for Intelligent Tutoring Systems* at ITS2002, 33-44.
- [26] Khan, T., and Brown, K. (2000). Model-based Training of Situated Skills. *British Journal of Educational Technology* vol. 31, 171-179.
- [27] Khan, T., Laine, S., Brown, K., Leitch, R., and Ritala, R. (1999). Multiple Model-based Explanations for Industrial Decision Support, in *Computational Intelligence for Modelling, Control and Automation*, (Mohammadian, M., ed.). IOS Press, 318-323.
- [28] Khan, T., Brown, K., and Leitch, R. (1999). Managing Organisational Memory with a Methodology Based on Multiple Domain Models, in *Proceedings of the Second International Conference on Practical Application of Knowledge Management*, 57-76.
- [29] Khan, T., Mitchell, J., Brown, K., and Leitch, R. (1998). Situated Learning using Descriptive Models. *International Journal of Human-computer Studies* vol. 49, 771-796.
- [30] Kuchta, D. (2000). Fuzzy Capital Budgeting. *Fuzzy Sets and Systems* vol. 111, 367-385.
- [31] Kuipers, B. (1994). *Qualitative Reasoning: Modelling and Simulation with Incomplete Knowledge*. MIT Press.
- [32] Kuo, R., Chen, C., and Hwang, Y. (2001). An Intelligent Stock Trading Decision Support System through Integration of Genetic Algorithm Based Fuzzy Neural Network and Artificial Neural Network. *Fuzzy Sets and Systems* vol. 118, 21-45.
- [33] Liu, P. (2001). Universal Approximations of Continuous Fuzzy-valued Functions by Multi-layer Regular Fuzzy Neural Networks. *Fuzzy Sets and Systems* vol. 119, 313-320.
- [34] Medsker, L. (1995). *Hybrid Intelligent Systems*. Kluwer Academic.
- [35] Östermark, R. (1996). A Fuzzy Control Model for Dynamic Portfolio Management, *Fuzzy Sets and Systems* vol. 78, 243-254.
- [36] Pan, Z., Liu, X., and Mejabi, O. (1997). A Neural-fuzzy System for Financial Forecasting. *Journal of Computational Intelligence in Finance* vol. 5, 7-15.
- [37] Pike, R., (1996). A Longitudinal Survey on Capital Budgeting Practices. *Journal of Business, Finance and Accounting* vol. 23, 79-92.
- [38] Ribeiro, R., Zimmermann, H.-J., Yager, R., and Kacprzyk, J., eds. (1999). *Soft Computing in Financial Engineering*. Physica-Verlag.
- [39] Sangster, A. (1993). Capital Investment Appraisal Techniques: A Survey of Current Usage. *Journal of Business, Finance and Accounting* vol. 20, 307-332.
- [40] Serguieva, A., and Hunter, J., Fuzzy Interval Methods in Investment Risk Appraisal. *Fuzzy Sets and Systems*, forthcoming.
- [41] Serguieva, A., and Kalganova, T. (2002). A Neuro-fuzzy-evolutionary Classifier of Low-risk Investments, in *Proceedings of the World Congress on Computational Intelligence*, FUZZ-IEEE: 997-1002.
- [42] Serguieva, A., Kalganova, T., and Hunter, J. (2001). Soft Computing in Investment Risk Appraisal, in *Proceedings of the International Conference of the European Society in Fuzzy Logic and Technology*, 214-219.
- [43] Serguieva, A., and Hunter, J. (2000). Investment Risk Appraisal. *Brunel Department of Economics and Finance Working Papers* vol. 00-15.
- [44] Simon, H. (1996). *Sciences of the Artificial*, 3rd ed. MIT Press.
- [45] Stulz, R. (1999). What is Wrong with Modern Capital Budgeting? *Address delivered at the Eastern Finance Association meeting in Miami Beach*.
- [46] Tanaka, H., Guo, P., and Türksen, B. (2000). Portfolio Selection Based on Fuzzy Probabilities and Possibilities Distributions. *Fuzzy Sets and Systems* vol. 111, 387-397.
- [47] Tay, N., and Linn, S. (2001). Fuzzy Inductive Reasoning, Expectation formation and the Behaviour of Security Prices. *Journal of Economic Dynamics and Control* vol. 25, 321-361.
- [48] Treleaven, P., and Goonatilake, S. (1995). *Intelligent Systems for Finance and Business*. Wiley.

- [49] Turing, A., Gandy, R. (ed.), and Yates, C. (ed.) (2001). *Collected Works of A.M. Turing: Mathematical Logic*. North-Holland.
- [50] Werbos, P. (1994). *The Roots of Backpropagation*. Wiley.
- [51] White, H. (1992). *Artificial Neural Networks*. Blackwell.
- [52] Yage, R., and Zadeh, L. (1994). *Fuzzy Sets, Neural Networks, and Soft Computing*. Thomson Press.
- [53] Zadeh, L., and Kacprzyk, J., eds. (1992). *Fuzzy Logic for the Management of Uncertainty*. Wiley.
- [54] Zimmermann, H.-J. (2001). *Fuzzy Set Theory – and Its Applications*. Kluwer Academic.

Appendix

A1. Formulating the fuzzy valued criterion

Preliminary: Let us consider the loglinear approximation of the price-dividend relation under time-varying returns,

$$r_{t+1} \approx \delta + p_{t+1} + (1-\lambda)dy_{t+1} - p_t,$$

where p_{t+1} , r_{t+1} and dy_{t+1} stand for the log share price, log return and log dividend yield, correspondingly. If the equation is solved forward for the log stock price, the following estimation is produced in period $t=0$,

$$\hat{p}_0 = \sum_{i=1}^T \lambda^{i-1} [(1-\lambda)(dy_i + p_i) + \delta - r_i] + \lambda^T p_T,$$

$$1 < e^p - \text{quotes in pence}, 1 < e^r < 2, 0 < e^{dy_i} < 1, p_i > 0, 0 < r_i < \ln(2), dy_i < 0,$$

where the parameters of linearisation, δ and λ , are evaluated with continuous functions of (dy_1, \dots, dy_T) . If the investment horizon is T , then a project is profitable at $t=0$ when the estimated share price exceeds the market share price, $\hat{p}_0 > p_0$. Based on this, the fuzzy valued criterion is formulated following a procedure in four steps.

Step 1: For each project, parameters δ and λ are considered crisp and obtained from

$$\lambda \equiv \left(1 + e^{\frac{1}{T} \sum_{i=1}^T dy_i} \right)^{-1} = f_1(dy_1, \dots, dy_T), 0 < \lambda < 1,$$

$$\delta \equiv (1-\lambda) \ln(1-\lambda) - \lambda \ln(\lambda) = f_2(dy_1, \dots, dy_T), 0 < \delta < 1.$$

Step 2: Market uncertainty is introduced applying initially a calibration technique based on the 95% confidence interval of Student's distribution t for the market level data. Thus, triangular fuzzy numbers are produced corresponding to fatter-tail possibility distributions. Then, the level-log data transformation causes nonlinear rather than triangular membership functions for the fuzzy log share prices \tilde{P}_i , rates of return \tilde{R}_i and dividend yields $\tilde{D}Y_i$, $1 \leq i \leq T$, $1 \leq i \leq N$. Here T is the investment horizon and N is the number of projects. Finally, positive nonlinear fuzzy coefficients $\tilde{A}_i, \tilde{B}_i, \tilde{C}_i$ are obtained from

$$\tilde{A}_i = \frac{1}{N} \sum_{i=1}^N \frac{\tilde{P}_i}{P_i}, \tilde{B}_i = \frac{1}{N} \sum_{i=1}^N \frac{\tilde{R}_i}{r_i}, \tilde{C}_i = \frac{1}{N} \sum_{i=1}^N \frac{D\tilde{Y}_i}{dy_i}, 1 \leq i \leq T,$$

and the initial calibration is slightly modified, assuming

$$\tilde{P}_i = \tilde{A}_i p_i, \tilde{R}_i = \tilde{B}_i r_i, D\tilde{Y}_i = \tilde{C}_i dy_i, 1 \leq i \leq T, 1 \leq i \leq N.$$

Step 3: The fuzzy log share price \tilde{P} at $t_0=0$ is presented as

$$\tilde{P}_0 = \sum_{i=1}^T \lambda^{i-1} [(1-\lambda)(\tilde{C}_i dy_i + \tilde{A}_i p_i) + \delta - \tilde{B}_i r_i] + \lambda^T \tilde{A}_T p_T = [\tilde{A}_T p_T (1-\lambda)] + \dots + [\tilde{A}_T p_T \lambda^{T-1}] - [\tilde{B}_T r_T] - \dots - [\tilde{B}_T r_T \lambda^{T-1}] + [\tilde{C}_T dy_T (1-\lambda)] + \dots + [\tilde{C}_T dy_T \lambda^{T-1} (1-\lambda)] + \left[\sum_{i=1}^T \lambda^{i-1} \delta \right] = A_T g_{AT} + \dots + \tilde{A}_T g_{AT} - \tilde{B}_T g_{BT} - \dots - \tilde{B}_T g_{BT} + \dots + \tilde{C}_T g_{CT} + g, \quad 0 < \lambda, \delta < 1,$$

where $g_{AT} = g_{AT}(x), g_{BT} = g_{BT}(x), g_{CT} = g_{CT}(x), g = g(x), x = (p_1, \dots, p_T, r_1, \dots, r_T, dy_1, \dots, dy_T), 1 \leq t \leq T, p_i > 0, 0 < r_i < \ln(2), dy_i < 0,$

are continuous functions defined on the market data employed to evaluate a project. Thus, the fuzzy log share is described as a continuous multivariable fuzzy-valued function.

Step 4: Applying the extension principle, the nonlinear membership function of the solution is defined by

$$\mu(y_P / \tilde{P}_0) = \sup \{ \alpha / y_P \in \Omega_{P_0}(\alpha) \}, \quad \Omega_{P_0}(\alpha) = \{ a_i g_{AT}(x) + \dots + c_T g_{CT}(x) + g(x) / a_i \in \tilde{A}_i(\alpha), \dots, c_T \in \tilde{C}_T(\alpha), x = (p_1, \dots, dy_T) \},$$

and for the specific formulation of \tilde{P}_0 , the α -cut $\Omega_{P_0}(\alpha)$ is equivalent to the interval arithmetic solution

$$\Omega_{P_0}(\alpha) = [\underline{P_0}(\alpha), \overline{P_0}(\alpha)],$$

$$\begin{aligned} P_0(\alpha) &= \underline{A}_I(\alpha)g_{A_I}(x) + \dots + \underline{A}_T(\alpha)g_{A_T}(x) - \overline{B}_I(\alpha)g_{B_I}(x) - \dots - \overline{B}_T(\alpha)g_{B_T}(x) + \overline{C}_I(\alpha)g_{C_I}(x) + \dots + \overline{C}_T(\alpha)g_{C_T}(x) + g(x), \\ \overline{P}_0(\alpha) &= \overline{A}_I(\alpha)g_{A_I}(x) + \dots + \overline{A}_T(\alpha)g_{A_T}(x) - \underline{B}_I(\alpha)g_{B_I}(x) - \dots - \underline{B}_T(\alpha)g_{B_T}(x) + \underline{C}_I(\alpha)g_{C_I}(x) + \dots + \underline{C}_T(\alpha)g_{C_T}(x) + g(x), \\ A_I(\alpha) &> 0, B_I(\alpha) > 0, C_I(\alpha) > 0, g_{A_I}(x) > 0, g_{B_I}(x) > 0, g_{C_I}(x) < 0, g(x) > 0, x = (p_1, \dots, dy_T), 1 \leq t \leq T. \end{aligned}$$

A2. Identifying the network structure

Remark 1: Let $f : U_1 \times \dots \times U_k \rightarrow \mathcal{R}$ is a multivariable continuous crisp function on the compact sets $U_i \subset \mathcal{R}$, $1 \leq i \leq k$. If $\tilde{A} \in F_0(\mathcal{R})$ is a fuzzy number and $F : U_1 \times \dots \times U_k \rightarrow F_0(\mathcal{R})$ is a multivariable fuzzy-valued function, where

$$F(x_1, \dots, x_k) = (\tilde{A}f)(x_1, \dots, x_k) = \tilde{A}f(x_1, \dots, x_k), x_i \in U_i, 1 \leq i \leq k,$$

then $F(x_1, \dots, x_k)$ is continuous on $U_1 \times \dots \times U_k$.

$$\text{Remark 2: Let } \mathfrak{S} \left\{ RFNN / RFNN(x_1, \dots, x_k) = \sum_{i=1}^q \tilde{V}_i * \left(\sum_{j=1}^m \tilde{E}_{ij} * \sigma \left(\sum_{\ell=1}^k \tilde{W}_{j\ell} * x_\ell + \tilde{\Theta}_j \right) \right) \right\}, q, m \in \mathcal{N}, \tilde{V}_i, \tilde{E}_{ij}, \tilde{W}_{j\ell}, \tilde{\Theta}_j \in F_0(\mathcal{R}) \left. \right\}$$

describes the class of four-layer regular fuzzy neural networks with sigmoid transfer functions and shift terms in the first hidden layer, and identity transfer functions with no shift terms in the second hidden layer. Restricting $\tilde{E}_{ij}, \tilde{W}_{j\ell}, \tilde{\Theta}_j \in F_0(\mathcal{R})$ to be $e_{ij}, w_{j\ell}, \theta_j \in \mathcal{R}$, the subset \mathfrak{S}_0 of \mathfrak{S} is obtained.

$$\mathfrak{S}_0 \left\{ RFNN / RFNN(x_1, \dots, x_k) = \sum_{i=1}^q \tilde{V}_i * \left(\sum_{j=1}^m e_{ij} * \sigma \left(\sum_{\ell=1}^k w_{j\ell} * x_\ell + \theta_j \right) \right) \right\}, q, m \in \mathcal{N}, \tilde{V}_i \in F_0(\mathcal{R}), e_{ij}, w_{j\ell}, \theta_j \in \mathcal{R} \left. \right\}.$$

Then \mathfrak{S} and \mathfrak{S}_0 are universal approximators for the multivariable continuous fuzzy-valued function $F : U_1 \times \dots \times U_k \rightarrow F_0(\mathcal{R})$ from Remark 1.

Remark 3: Let F_1, \dots, F_n are multivariable continuous fuzzy-valued functions as the one in Remark 1, then \mathfrak{S} and \mathfrak{S}_0 from Remark 2 are universal approximators for $F = \sum_{i=1}^n (\pm F_i)$.

Remark 4: The evaluated share price \tilde{P}_0 in equation (1) is a multivariable continuous fuzzy-valued function of the type in Remark 3. Consequently, there exists a four-layer regular fuzzy neural network $RFNN \in \mathfrak{S}_0$ approximating \tilde{P}_0 to an arbitrary degree of accuracy.

Regular network module evaluation: The extension principle and the interval arithmetic evaluation are equivalent for fuzzy networks of the identified class \mathfrak{S}_0 and the α -cuts $\Omega_{RFNN}(\alpha)$ of \tilde{P}_{RFNN} are computed from

$$\begin{aligned} \Omega_{RFNN}(\alpha) &= \left[\underline{P}_{RFNN}(\alpha), \overline{P}_{RFNN}(\alpha) \right], \quad \sigma_j = \sigma \left(\sum_{\ell=1}^T (w_{j\ell} p_\ell + u_{j\ell} r_\ell + z_{j\ell} dy_\ell) + \theta_j \right) > 0 \\ \underline{P}_{RFNN}(\alpha) &= \sum_{i=1}^q \min \left(\underline{V}_i(\alpha) * \left(\sum_{j=1}^m e_{ij} \sigma_j \right), \overline{V}_i(\alpha) * \left(\sum_{j=1}^m e_{ij} \sigma_j \right) \right), \quad \overline{P}_{RFNN}(\alpha) = \sum_{i=1}^q \max \left(\underline{V}_i(\alpha) * \left(\sum_{j=1}^m e_{ij} \sigma_j \right), \overline{V}_i(\alpha) * \left(\sum_{j=1}^m e_{ij} \sigma_j \right) \right). \end{aligned}$$

A3. Bidirectional incremental evolution: algorithm

- I:** Define the training set of projects $n \subset \mathcal{N}$ and obtain their \tilde{P}_0 from equation (1).
- II:** Choose the probing step of generations N_{gen} and the parameters $\xi_{DEC1}^{(k)}, \xi_{DEC2}^{(k)}, \xi_{DEC3}^{(k)}, \xi_{DEC4}^{(k)}, \xi_{DEC5}^{(k)}, \xi_{DECEND}^{(k)}, \xi_{INC}^{(k)}, \xi_{INCEND}^{(k)}$, (see subsection 2.3). Here $k = 1, 2, \dots$ is the corresponding level of decomposition and partitions are to be identified.
- III:** Initialise $k = 1$, $n^{(1)} = n$, and generate a random initial population IP_s of size s .
- IV:** Evolve the regular fuzzy neural network for N_{gen} generations, using the complete training set $n^{(k)}$. During evolution, evaluate \tilde{P}_{RFNN} from equation (1), and apply fitness function f_Q from definition (6).
- V:** Keep the result of the evolution - the breeding subpopulation $X_{s_j}^{(k)}$ - where s_j is the number of breeding chromosomes and $s_j < s$.
- VI:** Apply the objective function $\frac{1}{s_j} \sum_{i=1}^{s_j} \max(\xi(\chi_i)) - \xi_{DEC1}^{(k)} < 0$. If the average error over the breeding subpopulation $X_{s_j}^{(k)}$ in the complete training set is above the limit $\xi_{DEC1}^{(k)}$, then go to step III.
- VII:** Apply the objective function $\frac{1}{s_j} \sum_{i=1}^{s_j} \xi(\chi_i) - \xi_{DEC2}^{(k)} < 0$. If there do not exist single projects satisfying the condition, then generate a full-size population $IP_s \left(X_{s_j}^{(k)} \right)$ by recombination of $X_{s_j}^{(k)}$. Go to step IV.

- VIII: Group the single projects satisfying the condition in step VII into $n_i^{(k)}$ subsets of projects, $n_i^{(k)} = \{n_{i1}^{(k)}, \dots, n_{ij}^{(k)}, \dots, n_{iJ_k}^{(k)}\}$, where each $n_{ij}^{(k)}$ is of maximum size, subject to the condition $\frac{1}{s_j} \sum_{i=1}^{s_j} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) < \xi_{DEC2}^{(k)}$.
- IX: Partition the training set $n^{(k)}$ into $n^{(k)} = \{n_{11}^{(k)}, \dots, n_{1j}^{(k)}, \dots, n_{1J_k}^{(k)}, n_2^{(k)}\}$, where J_k is the number of subsets satisfying the objective function from step VIII. J_k is specific for the level of decomposition k . The subset of single projects not satisfying the condition in step VIII is $n_2^{(k)} = n^{(k)} / n_i^{(k)}$. In the extreme, it can be $n_2^{(k)} = \{\emptyset\}$ or $n_2^{(k)} = n^{(k)}$.
- X: Generate different full-size populations $IP_{s, 11} \left(X_{s_j}^{(k)} \right), \dots, IP_{s, 1J_k} \left(X_{s_j}^{(k)} \right)$ and $IP_{s, 2} \left(X_{s_j}^{(k)} \right)$ by recombination of the same breeding subpopulation $X_{s_j}^{(k)}$.
- XI: Evolve a separate neural network in N_{gen} generations for each training subset of $n^{(k)}$. Keep the evolution results – the breeding subpopulations $X_{s_j, 11}^{(k)}, \dots, X_{s_j, 1J_k}^{(k)}$ and $X_{s_j, 2}^{(k)}$.
- XII: If $\frac{1}{s_j} \sum_{i=1}^{s_j} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) < \xi_{DEC3}^{(k)}$, then generate a full-size population $IP_{s, 1j} \left(X_{s_j}^{(k)} \right)$. Else, go to step XIII.
- XIII: Evolve a fuzzy network, using the training set $n_{1j}^{(k)}$, until the average network error over the first half of the breeding subpopulation $X_{s_j/2}^{(k)}$ is less than ξ_{DECEND} . This means that the objective function is $\frac{2}{s_j} \sum_{i=1}^{s_j/2} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) < \xi_{DECEND}$. Keep the result of the evolution – half of the breeding subpopulation $X_{s_j/2, 1jEND}^{(k)}$.
- XIV: If $n_{1j}^{(k)}$ consists of a single project and $\xi_{DEC3}^{(k)} < \frac{1}{s_j} \sum_{i=1}^{s_j} \xi(\mathcal{X}_i) < \xi_{DEC2}^{(k)}$, then generate a new full-size population $IP_{s, 1j} \left(X_{s_j}^{(k)} \right)$. Else, go to step XV.
- XV: Evolve a regular fuzzy neural network for N_{gen} generations, using the training set $n_{1j}^{(k)}$. Keep the result of the evolution – the breeding subpopulation $X_{s_j, 1j}^{(k)}$. Go to step XI.
- XVI: If $\xi_{DEC3}^{(k)} < \frac{1}{s_j} \sum_{i=1}^{s_j} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) < \xi_{DEC4}^{(k)}$ and $n_{1j}^{(k)}$ consists of a subset of projects, then generate a full-size population $IP_{s, 1j} \left(X_{s_j}^{(k)} \right)$. Consider the subset $n_{1j}^{(k)}$ as a complete training set $n^{(k+1)} = n_{1j}^{(k)}$ and increase $k = k + 1$. Go to step IV.
- XVII: If $\xi_{DEC4}^{(k)} < \frac{1}{s_j} \sum_{i=1}^{s_j} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) < \xi_{DEC2}^{(k)}$ and $n_{1j}^{(k)}$ consists of a subset of projects, then generate a new full-size population $IP_{s, 11} \left(X_{s_j}^{(k)} \right)$. Consider the subset $n_{1j}^{(k)}$ as a complete training set and increase decomposition level $k = k + 1$. Go to step IV.
- XVIII: Apply objective function $\frac{1}{s_j} \sum_{i=1}^{s_j} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) - \xi_{DEC5}^{(k)} < 0$. If it is satisfied, then generate a full-size population $IP_{s, 2} \left(X_{s_j}^{(k)} \right)$, else generate a new initial population $IP_{s, 2} \left(X_{s_j}^{(k)} \right)$. Consider $n_2^{(k)}$ as a complete training set and increment $k = k + 1$. Go to step IV.
- XIX: If $n_2^{(k)}$ consists of a single project, then evolve a fuzzy network until the objective $\frac{2}{s_j} \sum_{i=1}^{s_j/2} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) < \xi_{DECEND}$ is met and keep the result $X_{s_j/2, 2END}^{(k)}$. Else consider $n_2^{(k)}$ as a complete training set, increment $k = k + 1$ and go to step IV.
- XX: Set k at the highest level of partition $k = K = \max(k)$. Consider the training set $n^{(k)} = \{n_{11}^{(k)}, \dots, n_{1J_k}^{(k)}, n_2^{(k)}\}$ and generate a full-size population $IP_{s, INC} \left(X_{s_j/2, 11END}^{(k)}, \dots, X_{s_j/2, 1J_kEND}^{(k)}, X_{s_j/2, 2END}^{(k)} \right)$.
- XXI: Evolve a fuzzy network, using the training set $n^{(k)}$, until $\frac{2}{s_j} \sum_{i=1}^{s_j/2} \max_{n_i^{(k)}}(\xi(\mathcal{X}_i)) - \xi_{INC} < 0$. Keep the result $X_{s_j/2, INC}^{(k)}$.
- XXII: Decrease $k = k - 1$, which is equivalent to increasing the incremental level. Consider the training set $n^{(k)} = \{n_{11}^{(k)}, \dots, n_{1J_k}^{(k)}, n_2^{(k)} = n^{(k+1)}\}$ and generate a full-size population $IP_{s, INC} \left(X_{s_j/2, 11END}^{(k)}, \dots, X_{s_j/2, 1J_kEND}^{(k)}, X_{s_j/2, INC}^{(k+1)} \right)$. If $k > 1$, go to step XXI.
- XXIII: Evolve a regular fuzzy neural network, using the training set $n^{(k)}$, until the error of the best chromosome gets below ξ_{INCEND} , $\max_{n_i^{(k)}}(\xi(\mathcal{X}_{INCEND}^{best})) - \xi_{INCEND} < 0$. Keep the best chromosome $\mathcal{X}_{INCEND}^{best}$. It represents the completely evolved network.

A4: Bidirectional incremental evolution: empirical results

During evolution apply fitness function $f_{\xi} = \begin{cases} 0, & \xi > 0.1515 \\ (0.1515 - \xi) * 1000 / 1.5, & \xi \leq 0.1515 \end{cases}$.

Decomposition part

a: Start with the training set $n^{(1)} = \{project1, project2, project3, project4, project5, project6\}$. Generate a random initial population IP_s of size $s = 100$, and evolve a fuzzy neural network for $N_{gen} = 10,000$ generations. The result for the first

objective function is $\frac{1}{s_1} \sum_{i=1}^{s_1} \max(\xi(\chi_i)) = 0.1276 < \xi_{DEC1}^{(1)} = 0.1525$. Consequently, keep the evolved breeding subpopulation $X_{s_1}^{(1)}$ of size $s_1 = 30$.

b: Check which single projects satisfy the second objective, $\frac{1}{s_1} \sum_{i=1}^{s_1} \xi(\chi_i) < \xi_{DEC2}^{(1)} = 0.0525$.

objective / project	project 1	project 2	project 3	project 4	project 5	project 6
$\frac{1}{s_1} \sum_{i=1}^{s_1} \xi(\chi_i)$	0.1255	0.1276	0.1114	0.1206	0.0972	0.0703

All six projects produce larger numbers then the parameter $\xi_{DEC2}^{(1)} = 0.0525$. Consequently, no partition is possible yet.

c: Generate a full-size population $IP_s(X_{s_1}^{(1)})$ by recombination of best subpopulation $X_{s_1}^{(1)}$ and continue training with $n^{(1)}$ for another $N_{gen} = 10,000$ generations.

objective / project	project 1	project 2	project 3	project 4	project 5	project 6	projects 1 & 5
$\frac{1}{s_1} \sum_{i=1}^{s_1} \xi(\chi_i)$	0.0448	0.0739	0.0691	0.0633	0.0472	0.0531	0.0557

Now the value for project 1 is less then the second parameter $\xi_{DEC2}^{(1)} = 0.0525$ and so is the value for project 5, while both projects together produce a larger number then 0.0525. Consequently, the following first-level decomposition is identified.

Level1: $n^{(1)} = \{n_{11}^{(1)}, n_{12}^{(1)}, n_2^{(1)}\}$, $n_{11}^{(1)} = \{project 1\}$, $n_{12}^{(1)} = \{project 5\}$, $n_2^{(1)} = \{project 2, project 3, project 4, project 6\}$

Keep the resultant breeding subpopulation in $X_{s_1}^{(1)}$.

d: Generate different full-size populations $IP_{s_1}(X_{s_1}^{(1)})$, $IP_{s_2}(X_{s_1}^{(1)})$, $IP_2(X_{s_1}^{(1)})$ by recombination of the same breeding subpopulation $X_{s_1}^{(1)}$, and evolve a separate fuzzy network in $N_{gen} = 10,000$ generations for each training subset of $n^{(1)}$.

project 1	project 5	project 2&3&4&6
$\frac{1}{s_1} \sum_{i=1}^{s_1} \max(\xi(\chi_i)) = 0.0064 < \xi_{DEC3}^{(1)} = 0.0125$	$\frac{1}{s_1} \sum_{i=1}^{s_1} \max(\xi(\chi_i)) = 0.0036 < \xi_{DEC3}^{(1)} = 0.0125$	$\frac{1}{s_1} \sum_{i=1}^{s_1} \max(\xi(\chi_i)) = 0.0644 < \xi_{DEC3}^{(1)} = 0.0775$

Consequently, keep the evolved breeding subpopulations $X_{s_1}^{(1)}$, $X_{s_2}^{(1)}$ and $X_2^{(1)}$.

e: Generate full-size populations $IP_{s_1}(X_{s_1}^{(1)})$ and $IP_{s_2}(X_{s_2}^{(1)})$, and evolve a separate fuzzy neural net for each subset $n_{11}^{(1)}$ and $n_{12}^{(1)}$, until the average value of the network error ξ over the first half of the breeding subpopulation $X_{s_1/2}^{(k)}$ is less than ξ_{DECEND} .

project	objective	number of generations
project 1	$\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) = 0.002482 < \xi_{DECEND} = 0.0025$	9,014
project 5	$\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) = 0.0024996 < \xi_{DECEND} = 0.0025$	13,465

Consequently, keep the first half of the breeding subpopulations, $X_{s_1/2}^{(1)}$ and $X_{s_2/2}^{(1)}$. Their size is $s_1/2 = 15$.

f: Check which single projects, elements of $n_2^{(1)} = n^{(2)} = \{project2, project3, project4, project6\}$, satisfy the objective

$$\frac{1}{s_1} \sum_{i=1}^{s_1} \xi(\chi_i) < \xi_{DEC2}^{(2)} = 0.0225.$$

objective / project	project 2	project 3	project 4	project 6
$\frac{1}{s_1} \sum_{i=1}^{s_1} \xi(\chi_i)$	0.0644	0.0631	0.0608	0.0181

The value for project 6 is less than 0.0225. Consequently, the following second-level decomposition is identified.

Level2: $n^{(2)} = \{n_{11}^{(2)}, n_2^{(2)}\}$, $n_{11}^{(2)} = \{project 6\}$, $n_2^{(2)} = \{project 2, project 3, project 4\}$

g: Generate a full-size population $IP_{s_1}(X_{s_1}^{(1)})$ and evolve a separate network for $n_{11}^{(2)}$ until the average error ξ over the first half

of the breeding subpopulation $X_{s_1/2}^{(2)}$ is less than ξ_{DECEND} .

project	objective	number of generations
project 6	$\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) = 0.002468 < \xi_{DECEND} = 0.0025$	5,147

Consequently, keep half of the breeding subpopulation $X_{s_1/2}^{(2)}$.

h: Generate a full-size population $IP_s \left(X_{s_1/2}^{(1)} \right)$ and evolve for $N_{gen} = 10,000$ generations a separate network with the training set

$n_2^{(2)} = n^{(3)} = \{project\ 2, project\ 3, project\ 4\}$. The result for the next objective is $\frac{1}{s_1} \sum_{i=1}^{s_1} \max(\xi(\chi_i)) = 0.0638 < \xi_{DECI} = 0.064$.

Consequently, keep the evolved breeding subpopulation $X_{s_1}^{(3)}$.

i: Generate a full-size population $IP_s \left(X_{s_1}^{(3)} \right)$ and evolve further the network with $n^{(3)}$, for a multiple of N_{gen} generations, until

some of the elements of $n^{(3)}$ meets the objective $\frac{1}{s_1} \sum_{i=1}^{s_1} \xi(\chi_i) < \xi_{DEC2} = 0.0425$. Only after 40,000 generations we get the result.

objective / project	project 2	project 3	project 4	projects 3&4
$\frac{1}{s_1} \sum_{i=1}^{s_1} \xi(\chi_i)$	0.0554	0.0380	0.0381	0.0421

Project 3 and project 4 meet the condition. Moreover, they meet the condition together, as well. Consequently, the following third-level decomposition is identified.

Level3: $n^{(3)} = \{n_{11}^{(3)}, n_2^{(3)}\}$, $n_{11}^{(3)} = \{project\ 3, project\ 4\}$, $n_2^{(3)} = \{project\ 2\}$

j: Evolve a separate fuzzy neural network for $n_{11}^{(3)}$ and for $n_2^{(3)}$, until the average network error ξ over the first half of the breeding subpopulation $X_{s_1/2}^{(3)}$ is less than ξ_{DECEND} .

project	objective	number of generations
projects 3&4	$\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) = 0.002426 < \xi_{DECEND} = 0.0025$	1,403
project 2	$\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) = 0.002476 < \xi_{DECEND} = 0.0025$	1,312

Keep half of the breeding subpopulations, $X_{s_1/2}^{(3)}$ and $X_{s_1/2}^{(3)}$. This concludes the decomposition part of the bidirectional evolutionary strategy, as $n_2^{(3)}$ consists of a single project.

Incremental part

k: Consider the training set $n^{(3)} = \{n_{11}^{(3)}, n_2^{(3)}\}$ and generate a full-size population $IP_s \left(X_{s_1/2}^{(3)}, X_{s_1/2}^{(3)} \right)$. Evolve a network until the objective $\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) < \xi_{INC} = 0.002$ is met. Keep half of the resulting breeding subpopulation $X_{s_1/2}^{(3)}$.

projects	objective	number of generations
2&3&4	$\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) = 0.001962 < \xi_{INC} = 0.002$	1,918

l: Consider the training set $n^{(2)} = \{n_{11}^{(2)}, n_2^{(2)}\} = \{n_{11}^{(2)}, n^{(3)}\}$ and generate a full-size population $IP_s \left(X_{s_1/2}^{(2)}, X_{s_1/2}^{(3)} \right)$. Evolve

a network until another objective $\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) < \xi_{INC} = 0.002$ is satisfied. Keep the resulting half-subpopulation $X_{s_1/2}^{(2)}$.

projects	objective	number of generations
2&3&4&6	$\frac{2}{s_1} \sum_{i=1}^{s_1/2} \max(\xi(\chi_i)) = 0.001984 < \xi_{INC} = 0.002$	503

m: Consider the training set $n^{(1)} = \{n_{11}^{(1)}, n_{12}^{(1)}, n_2^{(1)}\} = \{n_{11}^{(1)}, n_{12}^{(1)}, n^{(2)}\}$ and generate a full-size population

$IP_s \left(X_{s_1/2}^{(1)}, X_{s_1/2}^{(2)}, X_{s_1/2}^{(3)} \right)$. Evolve a network until the error of the best chromosome is $\xi < \xi_{INCEND} = 0.0015$.

projects	objective	number of generations
1&2&3&4&5&6	$\xi = 0.0014904 < \xi_{INCEND} = 0.0015$	15,481

Keep the best chromosome χ_{INCEND}^{best} . It represents the fully evolved fuzzy neural network.